

## MODULAR

## LONGRAIN

## Technical

Country of Origin	Australia
Description	Patterned Muti-Loop Pile Tile
Colours	7 Standard colours
Yarn	100% Statron Solution Dyed Nylon
Dye Method	Solution Dyed
Pile Weight	619g/m <sup>2</sup> (18oz)
Gauge	47.2/10cm (1/12 <sup>th</sup> gauge)
Tile Thickness	approx 7 mm
Backing Structure	Enviro Bac <sup>TM</sup>
Standard Tile Size	50cm x 50cm
Backing Options	Enviro Bac Plus <sup>TM</sup> [Cushion Bac]
(minimum quantities apply)	EasyGrip <sup>TM</sup>
Installation Methods	Recommend : Quarter Turn or Ashlar

## Performance

Anti-Static	AATCC 134 <3.5 kilovolts at 21°C and 20% relative humidity
Flammability Rating	CHF kW/m <sup>2</sup> **
(AS ISO 9239.1.2003)	Smoke value % minimum
Dimensional Stability	Less than 0.2%
(Heat + Water)	
Light Reflectance Values	Available upon request
Stain Treatment	Stain Warden <sup>TM</sup>
Biocontaminant Control	Bioshield <sup>TM</sup> Antimicrobial Treatment
ACCS Rating	Contract Heavy Duty & Stairs #
Warranty	12 Year*

## Sustainability

PVC Minimisation	<b>100% PVC FREE</b>
Recycled Content	Minimum of 60% recycled content in the backing structure. Minimum of 40% recycled content by weight of the product.
Indoor Air Quality	Green Building Council & Green Label Plus compliant for VOC's emission rate limits. **
Product Stewardship/End of Life	This product is <b>RECYCLABLE</b> and qualifies for take back at end of life under the Godfrey Hirst Product Stewardship Program.
Green Star	Environmental Certification Scheme <b>(ECS) Level 4</b> – 100% maximum points Certificate # **
Accreditation	Member of the Green Building Council of Australia Manufactured under Godfrey Hirst's management system certified as complying with ISO9001 & ISO14001



Winner Premier's Sustainability Awards 2011

All product specifications and colourations are subject to nominal manufacturing tolerances.  
Materials supply and/or manufacturing process may be changed without notice.  
As part of Godfrey Hirst's continuous improvement program, Godfrey Hirst reserve the right to change the specifications of or delete colours of this product without notice.  
All Godfrey Hirst Modular products must be installed in accordance with AS 2455 (Parts 1 & 2) and in conjunction with Godfrey Hirst's Installation Guidelines.  
Godfrey Hirst does not guarantee modular tile products that have been installed over a separate underlay

\* Terms and conditions apply      \*\*Test results and certificates are available on request.

0212