



Landscape – Specifications

Technical	
Country of Origin	Australia
Description	Tufted Textured Loop Pile Tile
Yarn	100% Statron™ Solution Dyed Nylon (SDN)
Colours	6 Standard
Pile Weight	680g/m ² (22oz) (±5% Tolerance)
Gauge	39.4/10cm (1/10 th gauge)
Dimensional Stability	
Backing Structure	Enviro Bac™ Minimum 60% Recycled Content
Standard Tile Size	50cm x 50cm (±0.5mm)
Installation Method	¼ Turn  Brick 

Performance	
Anti-Static	AATCC 134 <3.5 kilovolts at 21°C and 20% relative humidity
Flammability Rating (AS ISO 9239.1.2003)	CHF 6.9 kW/m ² ** (indicative only, direct stick) Smoke value 374% minimum
Stain Treatment	Stain Warden™
Biocontaminant Control	Bioshield™ Antimicrobial Treatment
ACCS Rating	Contract Extra Heavy Duty & Stairs
Warranty	15 Year*

Sustainability	
PVC Minimisation	100% PVC FREE
Recycled Content	Minimum of 60% recycled content in the backing structure. Minimum of 40% recycled content by weight of the product.
Indoor Air Quality	Green Building Council & Green Label Plus compliant for VOC's emission rate limits. **
Product Stewardship/End of Life	This product is RECYCLABLE and qualifies for take back at end of life under the Godfrey Hirst Product Stewardship Program.
Green Star	Environmental Certification Scheme (ECS) Level 4 – maximum points Certificate #TBA **
Accreditation	Member of the Green Building Council of Australia Manufactured under Godfrey Hirst's management system certified as complying with ISO9001 & ISO14001

All product specifications and colourations are subject to nominal manufacturing tolerances.
 Materials supply and/or manufacturing process may be changed without notice.
 All Godfrey Hirst Modular products must be installed in accordance with AS 2455 (Parts 1 & 2) and in conjunction with Godfrey Hirst's Installation Guidelines.
 * Terms and conditions apply
 **Test results and certificates are available on request.